

VELCRO® Brand

# ALFA-LOK™ Fastener with **AFC** SilverTape® 5345 General Purpose






## Features


- Free positionable, re-closable fastening system
- High Performance double sided acrylic foam tape
- Suitable for high and medium surface energy material such as glass, metals and several plastics

## Compatibility Surfaces

SUBSTRATES	VELCRO® Brand ALFA-LOK™ Fastener
GLASS	+
ALUMINUM (ANODIZED, RAW)	+
STEEL (STAINLESS, GALVANIZED)	+
PLYWOOD/MDF	+
FORMICA (POLISHING SIDE)	+
CARDBOARD	+
PAINTED WALLBOARD	+
CONCRETE	+
STONE	+
ABS	+
POLYESTER	+
VINYL	+
POLYACRYLIC/PMMA	+
POLYCARBONATE	+
POLYETHYLENE	-
POLYPROPYLENE	-
FABRICS	-

## Performance Specifications

Testing	Minimum Value
<b>BASE MATERIAL</b>	Modified Solvent based Acrylic Polymer
<b>ADHESIVE COLOUR</b>	White
 <b>TEMPERATURE RANGE OF USE</b>	Long Term: From -40 °C to +90 °C Short Term: 120 °C
 <b>PEEL 180° ADHESION (FINAT-FTM 01) (AVERAGE)</b>	11 N/cm * 14 N/cm * - (after 24 h)
<b>SOFTENING POINT</b>	90 °C
 <b>STATIC SHEAR (ASTM 3654)**</b>	1,000 gr. at 22 °C 500 gr. at 66 & 93 °C
<b>TACK</b>	Medium/Low
<b>APPLICATION METHOD</b>	Pressure
<b>APPLICATION</b>	High and medium surface energy, general use




\* Average according typical values.  
The specifications are as a reference and are pending to confirm.  
\*\* Weight that ½ square inch will hold 10,000 minutes (7 days).

VELCRO® Brand

## ALFA-LOK™ Fastener Closure Characteristics

 **SELF-ENGAGING MUSHROOM**

CHARACTERISTICS	VELCRO® Brand ALFA-LOK™ Tape
DENSITY	48 heads/cm <sup>2</sup>
CONSTRUCTION	Woven quadrilobal mushroom tape
BASE MATERIAL	<b>Base:</b> Polyester
	<b>Mushrooms:</b> Polypropylene
FASTENER	Self-engaging
CYCLE LIFE	-
 <b>PEEL STRENGTH (AVERAGE)</b>	2 N/cm
 <b>SHEAR STRENGTH (AVERAGE)</b>	50 N/cm <sup>2</sup>
 <b>TENSILE DISENGAGEMENT (AVERAGE)</b>	40 N/cm <sup>2</sup>
STANDARD COLOURS	Black
STANDARD WIDTHS	25mm
STANDARD PUT-UPS	25m rolls with flanges
	Cut pieces (customized)



### GLOBAL SERVICES

Velcro Group Corporation  
265 Franklin Street – 19th floor  
Boston – MA 02110  
USA  
Tel: (+617) 946 5501  
Velcro.com

### AMERICAS

**USA**  
Velcro USA Inc.  
Tel: (+800) 225 0180  
marketing@velcro.com  
Velcro.com

#### Canada

Velcro Canada Inc.  
Tel: (+800) 683 5276  
canada@velcro.com  
Velcro.com

#### Mexico

Velcro de México, S.A. de C.V.  
Tel: (+52) 55 5005 3300  
velcrodemexico@velcro.com  
Velcrodemexico.com

#### Brazil

Velcro Brasil Ltda.  
São Paulo  
Tel: (+55) 11 4195 6644  
contato@velcro.com  
Velcro.com.br

#### Sapiranga

Tel: (+55) 51 3599 1483  
contato@velcro.com  
Velcro.com.br

#### Uruguay

Velcro Industrial  
del Uruguay S.A.  
Tel: (+598) 2288 0008  
infovurg@velcro.com  
Velcro.com

### EMEA

#### Spain

Velcro Europe S.A.  
Tel: (+34) 93 758 32 98  
infovesa@velcro.com  
Velcro.es

#### Germany

Velcro GmbH  
Stuttgart  
Tel: (+49) 7141 991 19-0  
infovgmbh@velcro.com  
Velcro.de

#### Gronau

Tel: (+49) 2562 96 45-0  
infovgmbh@velcro.com  
Velcro.de

#### France

Velcro Industries France S.A.S.  
Tel: (+33) 1 34 38 78 88  
infovif@velcro.com  
Velcro.fr

#### Belgium

Alfatex N.V.  
Tel: (+32) 9 386 12 18  
infofobe@velcro.com  
Alfatex.com

#### Italy

Velcro Italia, S.R.L.  
Tel: (+39) 039 62 70 01  
infoveit@velcro.com  
Velcro.it

#### UK

Velcro Ltd.  
Tel: (+44) 1606 73 88 06  
infovlt@velcro.com  
Velcro.co.uk

#### Poland

Alfatex Sp. z o.o.  
Tel: (+48) 71 798 57 89  
infovpl@velcro.com  
Alfatex.pl

### APAC

#### Australia

Velcro Australia Pty. Ltd.  
Tel: (+61) 3 9703 2466  
sales@velcro.com.au  
Velcro.com.au

#### China

Velcro China Fastening  
Systems Company Limited  
Tel: (+86) 21 6045 2090  
(Shanghai Sales Office)  
chinamarketing@velcro.com  
Velcro.com.cn

#### Hong Kong

Velcro Hong Kong Ltd.  
Tel: (+852) 2570 3698  
hkenquiry@velcro.com  
Velcro.com.hk