



## TECHNICAL DATA

### ULTRA-MATE® 866

#### Construction Characteristics

Construction  
 Base Material  
 Width: CFM  
 Slitted tape  
 Overall thickness  
 Weight  
 Colour  
 Hooks / cm<sup>2</sup>

#### Usage Characteristics

Peel Strength with Velour std \*  
 Shear Strength with Velour std \*  
 Breaking Strength \*  
 Melting point  
 Washing resistance  
 U.V. resistance  
 Acid resistance  
 Humidity resistance  
 Sewn resistance  
 Flammability (MVSS302)

\* Internal norm of VESA

Extruded
Polypropylene
Nominal ± 1 % Nominal ± 1 mm
0.90 ± 0.15 mm
225 ± 20 g/m <sup>2</sup>
Natural
Media 137
Minimum 0.6 N/cm
Minimum 8.0 N/cm <sup>2</sup>
Average 100 N/cm
150°C
Good Low Medium Medium Low
Maximum 200 mm/minute

The information included in this Technical Sheet is based on reliable tests and trials. Average value as a reference only, not a nominal specification. Given the diversity of uses of our products we advise our customers to assure themselves that the product meets the requirements of their application. The responsibility for the application and use of the product remains with the customer.

**Elaborado:** J.C. Lima

**Revisado:** E. Ducet

**Autorizado:** J. Jacobs

**Fecha:** 13.10.11

**ANEXO: IDT – 605-B**

**FTP 616 Versión 3**