



## Vel.loc 085

### Construction characteristics

Basic construction  
Base material  
Standard binder backing

Width - Slitted tape  
- Tape with selvedges

Heads / cm<sup>2</sup>: width tape < 160mm  
160mm  
> 160mm

Overall thickness

Weight

### Usage characteristics

Peel Strength with Velour std \*

Shear Strength with Velour std \*

Cycle life \*

Breaking Strength \*

Shrinkage after washing ( 3 x 60°C ) \*

Melting point

Colourfastness to washing UNE-EN ISO 105-C10  
Colourfastness to dry cleaning ISO 105 sec/DO1  
Colourfastness to rubbing ISO 105 sec/X12  
Colourfastness to water ISO 105 sec/EO1  
Colourfastness to sea water ISO 105 sec/EO2  
Colourfastness to light ISO 105 sec/BO2  
Colourfastness to perspiration ISO 105 sec/EO4

\* Internal norm of VESA

The information included in this Technical Sheet is based on reliable tests and trials. Average value as a reference only, not a nominal specification. Given the diversity of uses of our products we advise our customers to assure themselves that the product meets the requirements of their application. The responsibility for the application and use of the product remains with the customer.

**Elaborado:** J.C. Lima

**Revisado:** E. Ducet

**Autorizado:** J. Jacobs

**Fecha:** 11.10.11

**ANEXO: IDT – 605-B**

**FTP 400 Versión 3**